WWW.PROLECAUSTRALIA.COM.AU



あちちちち

6 FF

ELECTRICAL SWITCHBOARD AND ENCLOSURE HARDWARE

CATALOGUE

TABLE OF CONTENTS



01	ENCLOSURE KEYS		
02	QUARTER TURN LATCHES	7	
03	QUARTER TURN LOCKS (WINGKNOB'S ETC)	9	
04	HANDLES (L & T HANDLES, PADLOCKABLE SWING HANDLES)	11	
05	LOCK RELATED ACCESSORIES	15	
06	DOOR STAYS	17	
07	HINGES	18	
08	THUMB SCREWS & LOCATING PINS	20	
09	EARTH & NEUTRAL BARS	21	
10	LOW VOLTAGE INSULATORS	22	
11	DOOR GASKETS (NEOPRENE TAPE & PINCHWELD)	23	



PRODUCT STATEMENT

Prolec Australia are specialist's in manufacturing custom solutions designed to thrive in Australia's harshest environments. Our diverse range of enclosures, formulated from robust materials, are purpose-built to endure challenging scenarios in any environment.


At Prolec Australia, our customised products integrate high-quality accessories to suit your individual needs at a competitive price. From heavy-duty handles and locks to specialised switchboard hardware, these products are the same high quality components we use to manufacture Australia's toughest enclosures & cabinets.

We provide exceptional craftsmanship that reflects the top-notch quality of our products. Our experts meticulously design these fit for purpose solutions and ensure particular care and attention to detail throughout the creation process.

PERFORMANCE GUIDELINES

Our catalogue showcases a range of products tailored for general industry applications. As every case varies, users need to conduct testing under their specific application conditions. This ensures the product is suitable for the intended function and desired performance. Prolec Australia recognises no warranties or representations concerning potential errors or exclusions in the provided product information.

Please note that Prolec Australia products may change design, dimensions, specifications, materials, or finishes without prior notice. It's recommended to verify the product details before making a purchase. If you require further information or product selection assistance, please contact our office.



INGRESS PROTECTION

Ingress Protection (IP) is an international standard (IEC 60529) used to rate the degree of protection or sealing effectiveness in electrical enclosures against intrusion of objects, water, dust or accidental contact. The IP rating consists of two key numbers: the first indicates protection against solid objects, while the second signifies defence against liquids. Understanding IP ratings crucial when selecting devices or equipment for specific environments. **See page 4 for more detailed information.


INGRESS PROTECTION (IP) RATING GUIDE




SOLIDS L	IQUIDS
There is no available data.	No protection.
No protection against ingress or contact of solids.	1 Protection against dripping water.
Protection against objects larger than 50mm.	2 protection against dripping water at a 15-degree angle.
Protection against objects larger than 12.5mm.	3 Protection against spraying water.
Brotection against objects larger than 2.5mm.	Protection against splashing water.
Protection against objects Iarger than 1mm.	5 Protection against water jets.
5 Protection against dust .	6 Protection against powerful water jets.
6 The unit is dust-tight .	Protection against water jets with higher pressure.
	7 Protection against being immersed in 1 meter of water.
IP 6 5	8 Protection against being immersed in at least 1 meter of water (or more).
Ingress Protection Solids (Dust etc.) Liquids (Water etc.)	Protection against powerful water jets with high temperatures

ENCLOSURE KEYS






5mm Double Bit, 8mm Square, 7mm Square, 8mm Triangle



ENCLOSURE KEYS





KEY-8MMTSam TriangleImage: Sector of the se

**If you require an enclosure key that is not listed above, contact our sales team for assistance with finding the right enclosure key to suit your requirements.



QUARTER TURN LATCHES



PQTL5DB	Quarter Turn Latch 5mm Double Bit Drive w/ CAM	Zinc Cast, Bright Chrome Finish
PQTL5DB-SS	Quarter Turn Latch 5mm Double Bit Drive w/ CAM	Stainless Steel Brushed Finish
(0)	22.5 Neoprene Gasket 18 18 10.00 3.00 Tongu	

5mm Pin "Double Bit" Barrel, IP65, Comes Standard with Cam 28 (see Page 16 for other options)

PQTL8T	Quarter Turn Latch 8mm Triangle Drive w/ CAM	Zinc Cast, Bright Chrome Finish
PQTL8T-SS	Quarter Turn Latch 8mm Triangle Drive w/ CAM	Stainless Steel Brushed Finish
	22.5 A 5 Cut out	

8mm Triangle Barrel, IP65, Comes Standard with Cam 28 (see Page 16 for other options)

PQTL8S	Quarter Turn Latch 8mm Square Drive w/ CAM	Zinc Cast, Bright Chrome Finish
PQTL8S-SS	Quarter Turn Latch 8mm Square Drive w/ CAM	Stainless Steel Brushed Finish
	22.5 45 18 20.1 Cut out Cut out	


8mm Square Barrel, IP65, Comes Standard with Cam 28 (see Page 16 for other options)

QUARTER TURN LATCHES



PQTL7S	Quarter Turn Latch 7mm Square Drive w/ CAM	Zinc Cast, Bright Chrome Finish
PQTL7S-SS	Quarter Turn Latch 7mm Square Drive w/ CAM	Stainless Steel Brushed Finish
(0)	22.5 45 20.1 Cut out Cut out Cut out Cam	

7mm Square Barrel, IP65, Comes Standard with Cam 28 (see Page 16 for other options)




8mm Square Slotted Barrel, IP65, Comes Standard with Cam 28 (see Page 16 for other options)




QUARTER TURN LOCKS






Quarter Turn Padlockable Collar Suitable for Most Standard Quarter Turn Locks.



WingKnob, Nut, Comes Standard with Cam 28 (see Page 16 for other options)



QUARTER TURN LOCKS



Black Keylockable Wing Knob Quarter Turn Lock Key type CL001 or 92268, Comes Standard with Cam 28 (see Page 16 for other options)



Poly Knob, Zinc Nut, Comes Standard with Cam 28 (see Page 16 for other options)



HANDLES




PPLSH-2	Padlockable Swing Handle	316 Stainless Steel Brushed Finish
PPLSH-CHROME	Padlockable Swing Handle	Zinc Die Cast, Bright Chrome Finish
	32 Tr Tr Tr Tr Tr Tr Tr Tr Tr Tr Tr Tr Tr	tout
Padlockable Swing Handle	e including CAM Wedge	
THANDLE-L-C TH	andle Lockable Quarter Turn - Small	Zinc Die Cast, Bright Chrome Finish
Chrome Lockable Keyed 92268 Quarter Turn, Comes Standard with Cam 28 (see Page 16 for other options)		
	T Handle Non-Locking Stainless Steel	
	State of the state	78 78 handle 032 19


316 Stainless Steel T Handle IP65, Comes Standard with Cam 28 (see Page 16 for other options)

HANDLES





Chrome T Handle Key Large Locking Concealed Rear Fixing with spindle Keyed 92268 or CL001



Chrome T Handle Large Non Locking Rear Fixing with Spindle



HANDLES



LHANDLE-KL-SS	L Handle, Keylockable Quarter Turn	Stainless Steel
LHANDLE-KL-C	L Handle, Keylockable Quarter Turn	Chrome

L Handle, Keylockable 1/4 Turn, Comes Standard with Cam 28 (see Page 16 for other options)



L Handle, Non-Lockable 1/4 Turn, Comes Standard with Cam 28 (see Page 16 for other options)

LHANDLE-PAD-CW-C L Handle, Padlockable 1/4 turn, Clockwise		Chrome
LHANDLE-PAD-AC-C	L Handle, Padlockable 1/4 turn, Anti-Clockwise	Chrome
	com 66 e32 i i i i i i i i i i i i i i i i i i i	

L Handle, Padlockable 1/4 turn, Comes Standard with Cam 28 (see Page 16 for other options)

HANDLES



115

LHANDLE-PAD-CW-S L Handle, Padlockable 1/4 Turn Clockwise W Spindle Chrome LHANDLE-PAD-AC-S L Handle, Padlockable 1/4 Turn Anti-clockwise W Spindle Chrome 30 60 15 L Handle, Padlockable Quarter Turn with Spindle



L Handle, Key/Padlockable, Rear Fixing with Spindle & Padlock Bracket (Clockwise & Anti-Clockwise Open)

www.prolecaustralia.com.au

CAMS & 3 POINT LOCKING RODS



2PT-CAM	2 Point Locking Cam Zinc Plated	Zinc Plated
2 Point Cam & Rod Ada	apters	2 4 5.5 - 19 3636
SP-CAM	Single Point Tongue Cam	Zinc Plated
0	5 Screw	R9 M8 Thread

QT CAMS	н	BH	Mild Steel as Standard (Stainless Steel Available on Request)
QT-CAM4	4MM	-14MM	H = Overall Height BH = Bend Height of Cam Only
QT-CAM14	14MM	-4MM	
QT-CAM18	18MM	омм	
QT-CAM20	20MM	2MM	
QT-CAM22	22MM	4MM	
QT-CAM25	25MM	7MM	
QT-CAM28	28MM	10MM	
QT-CAM36	36MM	18MM	E State Stat
QT-CAM41	41MM	23MM	
QT-CAM47	47MM	29MM	
QT-CAM50	50MM	32MM	(Assuming Lock Body is 18mm)

CAMS & 3 POINT LOCKING RODS



3PT-CAM	3 Point Locking Cam	Zinc Plated
3PT-CAM-SS	3 Point Locking Cam	Stainless Steel
	60 3.7	94

3 Point Locking Cam with Rod Adapters. 70mm Overall, 60mm from Shaft to End of Cam

LRMS1200NR	MS Locking Rod W Nylon Rollers	Mild Steel & Nylon
LRMS1200SR	MS Locking Rod W Stainless Steel Rollers	Mild Steel & Stainless Steel
LRSS1200SR	SS Locking Rod W Stainless Steel Rollers	All Stainless Steel
	1200	

Locking Rod, 1200mm (L), Stainless OR Mild Steel with Nylon Or Stainless Steel Rollers



(Customisable with your choice of available materials)

DOOR STAYS





HINGES



304 Grade Stainless Steel Hinge with Stainless Steel Removable Pin

B/OPINTLE-SS	Bolt on Pintle Hinge 82mm	Stainless Steel		
B/OPINTLE-C	Bolt on Pintle Hinge 82mm	Chrome		
<u> </u>		29 6 41		

82mm Brass Hinge Chrome/Stainless Steel Plated with Phillips Hex Head Screws Supplied

B/OPINTLE-82C3S	Bolt On Pintle Hinge 82mm W 3mm Step	Chrome	
B/OPINTLE-82SS3S	Bolt On Pintle Hinge 82mm W 3mm Step	Stainless Steel	
8 9 9	82	29 41 6	


82mm Brass Hinge Chrome/Stainless Steel Plated 3mm Step, with SS Pin, Phillips Hex Head Screws Supplied

HINGES



B/OPINTLE-82C8S	Bolt On Pintle Hinge 82mm W 8mm step	Chrome
0		29 41 8

82mm Brass Hinge Chrome Plated 8mm Step, with Stainless Steel Pin, Phillips Hex Head Screws Supplied




50mm Stainless Steel Hinge, with Stainless Steel Pin, Phillips Hex Head Screws Supplied.




304 Stainless Steel Lift Off Hinge 50mm x 76mm x 1.5mm 5mm Mounting Holes, 6.35mm Thick Pin


THUMB SCREWS & LOCATING PINS







M6 x 30mm Knurled Thumb Screw Chrome Plated with O-ring, (L)30mm x (A)24mm



EARTH & NEUTRAL BARS



PROENB-DE6	DE Range Neutral Bar 6 Way	Brass with Mild Steel & Brass Screws
PROENB-DE12	DE Range Neutral Bar 12 Way	Brass with Mild Steel & Brass Screws
PROENB-DE18	DE Range Neutral Bar 18 Way	Brass with Mild Steel & Brass Screws
PROENB-DE24	DE Range Neutral Bar 24 Way	Brass with Mild Steel & Brass Screws
PROENB-DE36	DE Range Neutral Bar 36 Way	Brass with Mild Steel & Brass Screws
PROENB-DE48	DE Range Neutral Bar 48 Way	Brass with Mild Steel & Brass Screws



6 Way, 10.5 x 1.9mm



12 Way, 14.5 x 1.9mm




18 Way, 18.5 x 1.9mm

24 Way, 23 x 1.9mm

36 Way, 32 x 1.9mm





DE Range Neutral Bar, 2 x M8 Screws for 165Amp Cables, 2 xM4 Posi-drive screws per numbered tunnel Bar.

LOW VOLTAGE INSULATORS



BBLV-OP-8	8/10	Low Voltag	ge Insulat	or		Glass	Reinford	ed Polye	ster
BBLV-OP-	12/8	Low Voltage Insulator			Glass Reinforced Polyester			ster	
BBLV-	OP-8/	/10			BBLV-0	OP-12/	/8		
н	D	A/F	Р		н	D	A/F	Р	
50	35	50	15		35	25	32	15	
Dielectric Rat	ting - 10	NKV, System	Voltage Ra	ting 1.1KV					

DOOR GASKETS (PINCHWELD)






DOOR GASKETS (PINCHWELD)



PINCH-SIDE-S Pinchweld & Rubber on Side - Small Metal Core, EPDM Foam Rubber 9.5



Rubber Sealing EPDM with Metal Core, Soft Foam Rubber, Black Large



Rubber Sealing EPDM with Metal Core, Soft Foam Rubber, Black Small

0

5





PINCH-BULB-SPONGE Pinchweld & Rubber Bulb Sponge Rubber EPDM, Metal Core

Rubber EPDM with Metal Core & Sponge Rubber Bulb, Black





DOOR GASKETS (ADHESIVE)



GSK-3/25MM	Gasket Foam 3x25mm W Adhesive Backing, 25m Roll	Neoprene
GSK-6.4/24MM	Gasket Foam 6.4x24mm W Adhesive Backing, 15m Roll	Neoprene
GSK-9.5/25MM	Gasket Foam 9.5x25mm W Adhesive Backing, 10m Roll	Neoprene



Gasket Foam, Expanded EPDM Sponge Rubber W Acrylic Adheasive. Quick Compression Recovery. Flame Retardant, Self Extingishing & CFC & HCFC Free.



Gasket Foam, Expanded EPDM Sponge Rubber W Acrylic Adheasive. Quick Compression Recovery. Flame Retardant, Self Extingishing & CFC & HCFC Free. (Custom Cut)



CONTACT US

P 02 4964 9660
E sales@prolecaustralia.com.au
335 TOMAGO ROAD, TOMAGO NSW 2322

Don't see what youre looking for? We have over 1000 products available on our website.

www.prolecaustralia.com.au

Our enclosures are proudly 100% Australian made in our Newcastle facility using only the highest quality materials.

At Prolec Australia we strive to meet your needs and guarantee all of our products. If you are not 100% satisfied with your enclosures, we will replace them free of charge.

*Conditions Apply

(7) (10) (10)